

Serial No. 10/699,904

Docket No. 200310791-1

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A system comprising:
a calculator that provides an indication of ~~a slack~~ slack for at least one node of a circuit design, the at least one node being capable of operating transparently and non-transparently, the indication of ~~the slack~~ slack being determined based on a minimum slack value for paths that include the at least one node, regardless of path transparency.
2. (Original) The system of claim 1, wherein at least one path that includes the at least one node is a non-transparent path based on timing information for the at least one path.
3. (Original) The system of claim 1, wherein the at least one node further comprises at least one latch.
4. (Original) The system of claim 1, wherein the at least one node further comprises a plurality of latches arranged to define at least one path, alternating latches along the at least one path being clocked by substantially out-of-phase clock signals to propagate a signal along the at least one path.
5. (Original) The system of claim 4, wherein the at least one path has a non-transparency based on timing information for the circuit design.
6. (Original) The system of claim 5, wherein the at least one path has at least one non-transparent latch based on the timing information.
7. (Original) The system of claim 1, further comprising a path tracer that traces each path that includes the at least one node, regardless of path transparency, the calculator determining slack for the paths traced by the path tracer.
8. (Original) The system of claim 7, wherein the path tracer traces through a downstream portion of at least one path that includes the at least one node, regardless of transparency of the at least one node.

Serial No. 10/699,904**Docket No. 200310791-1**

9. (Original) The system of claim 7, further comprising a potential slack calculator that ascertains a minimum slack value associated with the at least one node according to a minimum of the slack determined for the paths traced by the path tracer.
10. (Original) The system of claim 7, wherein at least one path through the at least one node operates non-transparently based on timing information provided by timing analysis for at least a portion of the circuit design.
11. (Original) The system of claim 1, further comprising a timing analysis system that provides timing information associated with circuit components for paths that include the at least one node, the slack calculator determining the indication of slack for the at least one node based on the timing information.
12. (Original) A computer implemented design tool comprising the system of claim 1.
13. (Previously Amended) A system to facilitate design of an integrated circuit, comprising:
a path tracer that traces paths associated with a given node of a circuit design, regardless of path transparency, the path tracer tracing an input path relative to the given node and at least one other path that includes the given node and a downstream portion relative to the given node; and
a calculator that determines slack characteristics associated with the traced paths associated with the given node based on timing information for the traced paths, a minimum slack characteristic being selected from the slack characteristics determined for the traced paths associated with the given node.
14. (Cancelled)
15. (Original) The system of claim 13, wherein the given node further comprises circuitry capable of operating transparently and non-transparently.
16. (Original) The system of claim 13, wherein at least one of the paths further comprises a plurality of latches arranged along the at least one of the paths, the plurality of latches being

Serial No. 10/699,904**Docket No. 200310791-1**

clocked by substantially out-of-phase clock signals to propagate a signal along the at least one of the paths.

17. (Original) The system of claim 13, wherein the at least one of the paths has a non-transparency according to corresponding timing information for the circuit design.

18. (Previously Amended) The system of claim 13, further comprising a potential slack calculator that determines a potential slack value as [[a]] the minimum slack characteristic that is associated with the given node according to the slack characteristics determined for each of the paths traced by the path tracer.

19. (Original) The system of claim 18, wherein at least one of the paths traced through the given node operates non-transparently based on the timing information.

20. (Original) The system of claim 13, further comprising a timing analysis system that provides the timing information associated with circuit components for the traced paths.

21. (Previously Amended) A system comprising:

means for tracing at least one path that includes a given node of a circuit design by analyzing the at least one path transparently, the given node being capable of operating transparently and non-transparently; and

means for determining potential slack for the given node, the potential slack corresponding to a minimum slack value determined from slack values associated with the given node, including a slack value associated with each of a plurality of paths that include the given node based on timing information for the plurality of paths.

22. (Original) The system of claim 21, further comprising means for determining slack for each of the paths traced by the means for tracing, the potential slack corresponding to minimum of the slack determined for paths traced by the means for tracing.

23. (Original) The system of claim 21, wherein the means for tracing is operative to trace each path associated with the given node regardless of path transparency.

Serial No. 10/699,904**Docket No. 200310791-1**

24. (Original) The system of claim 23, further comprising means for determining slack for each of the paths traced by the means for tracing, the potential slack corresponding to minimum slack value from the slack determined for each of the paths traced by the means for tracing.

25. (Original) The system of claim 21, wherein the at least one of the paths further comprises plural means for latching an input signal from an input port to an output port based on a clock signal, the plural means for latching arranged along the at least one path such that adjacent pairs of the means for latching are activated to propagate a signal therethrough with substantially out-of-phase clock signals.

26. (Original) The system of claim 21, further comprising means for performing timing analysis on a circuit design that includes the at least one path to provide the timing information associated with circuit components for the at least one path.

27. (Currently Amended) A computer-readable medium having computer-executable instructions for performing a method comprising:

computing ~~a clock~~ slack associated with a given node of a circuit design by analyzing each path associated with the given node transparently; and

determining a potential slack value as a minimum of the computed slack associated with the given node.

28. (Original) The computer-readable medium of claim 27, wherein the computing further comprises employing timing analysis information for the circuit design to compute the slack associated with the given node for each path associated with the given node.

29. (Original) The computer-readable medium of claim 27, wherein the given node is capable of operating transparently and non-transparently based on a control signal.

30. (Original) The computer-readable medium of claim 27, wherein at least one path associated with the given node comprises a plurality of latches arranged along the at least one path and being clocked by substantially out-of-phase clock signals for propagating a signal along the at least one path.

Serial No. 10/699,904**Docket No. 200310791-1**

31. (Original) The computer-readable medium of claim 27, further comprising computer-executable instructions for tracing at least one path associated with the given node to enable a corresponding slack computation for the at least one path regardless of path transparency.

32. (Previously Amended) A method comprising:

determining a slack characteristic for a first path associated with a node of a given circuit design;

determining the slack characteristic for at least a second path, regardless of path transparency, the second path including the node and at least a portion of the second path being capable of operating transparently and non-transparently; and

providing an indication of slack associated with the node according to a minimum of the slack characteristic for [[a]]the first path and the slack characteristic for the at least a second path.

33. (Original) The method of claim 32, wherein at least one of the first and second paths is a non-transparent path based on timing information associated with the circuit design.

34. (Cancelled)

35. (Previously Amended) The method of claim 32, further comprising employing timing information obtained for the circuit design to compute each slack characteristic as a respective slack value associated with the given node for each path associated with the node.

36. (Original) The method of claim 35, further comprising tracing each path associated with the node transparently to enable a corresponding slack computation for each path associated with the node regardless of path transparency.

37. (Original) The method of claim 32, wherein the node comprises circuitry capable of operating transparently and non-transparently.

38. (Original) The method of claim 32, wherein at least one of the first and second paths associated with the node comprises a plurality of latches arranged along the respective path in which each adjacent pair of the plurality of latches along the respective path are clocked by substantially out-of-phase clock signals for propagating a signal along the respective path.

Serial No. 10/699,904**Docket No. 200310791-1**

39. (Original) A computer-readable medium having computer-executable instructions for performing the method of claim 32.